Callington Haven

Chemwatch: **5147-39**Version No: **2.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 24/07/2014 Print Date: 31/07/2014 Initial Date: Not Available S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier Product name DUBL-CHEK BO-1 Aerosol Chemical Name Not Applicable Synonyms Not Available **AEROSOLS** Proper shipping name Chemical formula Not Applicable Other means of identification Not Available **CAS** number Not Applicable Relevant identified uses of the substance or mixture and uses advised against Application is by spray atomisation from a hand held aerosol pack Relevant identified uses Use according to manufacturer's directions. Details of the manufacturer/importer Callington Haven Registered company name 30 South Street Rydalmere 2116 **Address** NSW Australia Telephone +61 2 9898 2788 +61 2 9684 4215 Fax Website www.callingtonhaven.com Email sales@calhaven.com.au **Emergency telephone number** Association / Organisation Not Available 1800 039 008 (24 hours),+61 3 **Emergency telephone numbers** 9573 3112 (24 hours) 1800 039 008 (24 hours),+61 3 Other emergency telephone 9573 3112 (24 hours) numbers **CHEMWATCH EMERGENCY RESPONSE Primary Number Alternative Number 1** Alternative Number 2 1800 039 008 +612 9186 1132 Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Once connected and if the message is not in your prefered language then please dial 01

CHEMWATCH HAZARD RATINGS

Page 2 of 10 DUBL-CHEK BO-1 Aerosol

Issue Date: **24/07/2014**Print Date: **31/07/2014**



| Poisons Schedule | Not Applicable | | | |
|-----------------------------------|---|--|--|--|
| GHS Classification ^[1] | Aerosols Category 1, Skin Corrosion/Irritation Category 2, STOT - SE (Narcosis) Category 3 | | | |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI | | | |

Label elements

GHS label elements





| SIGNAL WORD | DANGER |
|-------------|---|
| | *************************************** |

Hazard statement(s)

| H222 | Extremely flammable aerosol | |
|--------|---|--|
| H315 | Causes skin irritation | |
| H336 | May cause drowsiness or dizziness | |
| AUH044 | Risk of explosion if heated under confinement | |
| AUH066 | Repeated exposure may cause skin dryness and cracking | |

Precautionary statement(s): Prevention

| • | | | | | |
|--|---|--|--|--|--|
| P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. | | | | | |
| P211 Do not spray on an open flame or other ignition source. | | | | | |
| P251 Do not pierce or burn, even after use. | | | | | |
| P271 | Use only outdoors or in a well-ventilated area. | | | | |

Precautionary statement(s): Response

| 4 | | | |
|--|--|--|--|
| P321 Specific treatment (see advice on this label). | | | |
| P312 Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. | | | |
| P302+P352 | IF ON SKIN: Wash with plenty of water and soap | | |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. | | |

Precautionary statement(s): Storage

| P405 | Store locked up. | |
|-----------|--|--|
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. | |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. | |

Precautionary statement(s): Disposal

| P501 | Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration |
|------|--|
|------|--|

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|------------|-----------|---|
| 64742-47-8 | 68 | distillates, petroleum, light, hydrotreated |

Issue Date: 24/07/2014 Print Date: 31/07/2014

DUBL-CHEK BO-1 Aerosol

| 68476-85-7. | 30 | hydrocarbon propellant |
|---------------|----|------------------------|
| Not Available | 1 | magnetic particles |

SECTION 4 FIRST AID MEASURES

Description of first aid measures

| - | |
|--------------|---|
| Eye Contact | If aerosols come in contact with the eyes: Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear. ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation. |
| Inhalation | If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. |
| Ingestion | If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- ▶ Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

SMALL FIRE:

► Water spray, dry chemical or CO2

LARGE FIRE:

► Water spray or fog.

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. Fire Incompatibility as ignition may result

Advice for firefighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- ▶ Liquid and vapour are highly flammable.

Fire/Explosion Hazard

- Severe fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Severe explosion hazard, in the form of vapour, when exposed to flame or spark.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

- · Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.
- **Major Spills**
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

Other information

- eject contents of can • Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may

No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container

- · Aerosol dispenser.
- Check that containers are clearly labelled.

Storage incompatibility

Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| GREDIENT DAIA | | | | | | | |
|------------------------------|---|-------------------------------|--------------------------|------------------|------------------|------------------|--|
| Source | Ingredient | Material name | TWA | STEL | Peak | Notes | |
| Australia Exposure Standards | distillates, petroleum, light, hydrotreated | Oil mist, refined mineral | 5 mg/m3 | Not Available | Not Available | Not Available | |
| Australia Exposure Standards | hydrocarbon propellant | LPG (liquified petroleum gas) | 1800 mg/m3 / 1000 ppm | Not Available | Not Available | Not Available | |

EMERGENCY LIMITS

| Ingredient | TEEL-0 | TEEL-1 | TEEL-2 | TEEL-3 |
|------------------------|----------|----------|----------|----------|
| hydrocarbon propellant | 1000 ppm | 2000 ppm | 2000 ppm | 2000 ppm |

| Ingredient | Original IDLH | Revised IDLH |
|---|------------------|-----------------|
| distillates, petroleum, light, hydrotreated | Not Available | Not Available |
| hydrocarbon propellant | 19,000 [LEL] ppm | 2,000 [LEL] ppm |
| magnetic particles | Not Available | Not Available |

Exposure controls

Appropriate engineering

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.

Well-designed engineering controls can be highly effective in protecting workers and will typically be inde-

Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection











- ▶ Safety glasses with side shields.
- Chemical goggles.

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

Hands/feet protection

- OTHERWISE:
- For potentially moderate exposures:Wear general protective gloves, eg. light weight rubber gloves.
- ▶ For potentially heavy exposures:
- ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.

No special equipment needed when handling small quantities.

Body protection

See Other protection below

Other protection

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- ▶ Skin cleansing cream.
- Eyewash unit.

Thermal hazards

Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

DUBL-CHEK BO-1 Aerosol Not Available

| Material | СРІ |
|----------|-----|
|----------|-----|

- * CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|---|--|-------------------------|-------------------------|
| up to 10 | 1000 | AX-AUS / Class1 | - |
| up to 50 | 1000 | - | AX-AUS / Class 1 |
| up to 50 | 5000 | Airline * | - |

Issue Date: 24/07/2014 Print Date: 31/07/2014

DUBL-CHEK BO-1 Aerosol

long-term or frequent use. A qualified practitioner should be consulted.

| up to 100 | 5000 | - | AX-2 |
|-----------|-------|---|-----------|
| up to 100 | 10000 | - | AX-3 |
| 100+ | | | Airline** |

^{* -} Continuous Flow ** - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| Appearance | 22aer Brown highly flammable liquid with petroleum odour; does not mix with water. | | |
|--|--|---|----------------|
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Applicable | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | -84 propellant | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Flammable. | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | 9.5 propellant | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | 1.8 propellant | Volatile Component (%vol) | >60 |
| Vapour pressure (kPa) | UNDER PRESSURE | Gas group | Not Available |
| Solubility in water (g/L) | Immiscible | pH as a solution(1%) | Not Applicable |
| Vapour density (Air = 1) | >1 | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| Reactivity | See section 7 |
|------------------------------------|--|
| Chemical stability | Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

Page 7 of 10

DUBL-CHEK BO-1 Aerosol

Issue Date: **24/07/2014**Print Date: **31/07/2014**

| | WARNING:Intentional misuse by concentrating/inhaling contents may be lethal. | |
|--------------------------------|--|---|
| Ingestion | Accidental ingestion of the material may be damaging to the health of the individual. Not normally a hazard due to physical form of product. Ingestion may result in nausea, abdominal irritation, pain and vomiting | |
| Skin Contact | This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing skin condition Open cuts, abraded or irritated skin should not be exposed to this material | |
| Eye | There is some evidence to suggest | that this material can cause eye irritation and damage in some persons. |
| Chronic | Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS] | |
| | | |
| DUDI QUEK DO 4 Assessal | TOXICITY | IRRITATION |
| DUBL-CHEK BO-1 Aerosol | Not Available | Not Available |
| distillates, petroleum, light, | TOXICITY | IRRITATION |
| hydrotreated | Not Available | Not Available |
| hydrogarhan mranallant | TOXICITY | IRRITATION |
| hydrocarbon propellant | Not Available | Not Available |

Not available. Refer to individual constituents.

| DISTILLATES, PETROLEUM, |
|-------------------------|
| LIGHT, HYDROTREATED |

Kerosene may produce varying ranges of skin irritation, and a reversible eye irritation (if eyes are washed). Skin may be cracked or flaky and/or leathery, with crusts and/or hair loss. It may worsen skin cancers. There may also be loss of weight, discharge from the nose, excessive tiredness, and wheezing.

HYDROCARBON PROPELLANT

No significant acute toxicological data identified in literature search. inhalation of the gas

| Acute Toxicity | 0 | Carcinogenicity | 0 |
|--------------------------------------|----------|--------------------------|---|
| Skin Irritation/Corrosion | ✓ | Reproductivity | 0 |
| Serious Eye Damage/Irritation | 0 | STOT - Single Exposure | ~ |
| Respiratory or Skin sensitisation | 0 | STOT - Repeated Exposure | 0 |
| Mutagenicity | 0 | Aspiration Hazard | 0 |

Legend:

- ✓ Data required to make classification available
- 🗶 Data available but does not fill the criteria for classification

CMR STATUS

| CARCINOGEN | hydrocarbon propellant | Australia Exposure Standards - Carcinogens | Carc. 1B |
|------------|------------------------|--|----------|
| CARCINOGEN | nydrocarbon propellant | Australia Exposure Standards - Carcinogens | Carc. 16 |

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

For Acetone: I og Kow : -0.24;

Half-life (hr) air : 312-1896;

Half-life (hr) H2O surface water : 20; Henry's atm m3 /mol : 3.67E-05 BOD 5: 0.31-1.76,46-55%

COD: 1.12-2.07 ThOD: 2.2BCF: 0.69.

Environmental Fate: The relatively long half-life allows acetone to be transported long distances from its emission source.

Atmospheric Fate: Acetone preferentially locates in the air compartment when released to the environment.

Issue Date: 24/07/2014 Print Date: 31/07/2014

DUBL-CHEK BO-1 Aerosol

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|---------------|-------------------------|------------------|
| Not Available | Not Available | Not Available |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|---------------|-----------------|
| Not Available | Not Available |

Mobility in soil

| Ingredient | Mobility |
|---------------|---------------|
| Not Available | Not Available |

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ▶ Consult State Land Waste Management Authority for disposal.
- ▶ Discharge contents of damaged aerosol cans at an approved site.
- ▶ Allow small quantities to evaporate.
- ▶ DO NOT incinerate or puncture aerosol cans.

SECTION 14 TRANSPORT INFORMATION

Labels Required



| Marine Pollutant | NO |
|------------------|-----|
| HAZCHEM | 2YE |

Land transport (ADG)

| UN number | 1950 |
|------------------------------|--|
| Packing group | Not Applicable |
| UN proper shipping name | AEROSOLS |
| Environmental hazard | No relevant data |
| Transport hazard class(es) | Class 2.1 Subrisk Not Applicable |
| Special precautions for user | Special provisions 63 190 277 327 Limited quantity See SP 277 |

Air transport (ICAO-IATA / DGR)

| UN number | 1950 | |
|------------------------------|---|---------------------|
| Packing group | Not Applicable | |
| UN proper shipping name | Aerosols, flammable | |
| Environmental hazard | No relevant data | |
| Transport hazard class(es) | ICAO/IATA Class 2.1 ICAO / IATA Subrisk Not Applicable ERG Code 10L | |
| Special precautions for user | Special provisions Cargo Only Packing Instructions | A145A167A802 203 |

| Cargo Only Maximum Qty / Pack | 150 kg |
|---|---------|
| Passenger and Cargo Packing Instructions | 203 |
| Passenger and Cargo Maximum Qty / Pack | 75 kg |
| Passenger and Cargo Limited Quantity Packing Instructions | Y203 |
| Passenger and Cargo Limited Maximum Qty / Pack | 30 kg G |

Sea transport (IMDG-Code / GGVSee)

| UN number | 1950 |
|------------------------------|---|
| Packing group | Not Applicable |
| UN proper shipping name | AEROSOLS |
| Environmental hazard | No relevant data |
| Transport hazard class(es) | IMDG Class 2.1 IMDG Subrisk See SP63 |
| Special precautions for user | EMS Number F-D , S-U Special provisions 63 190 277 327 344 959 Limited Quantities See SP277 |

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

distillates, petroleum, light, hydrotreated(64742-47-8) is found on the following regulatory lists

"Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index","Australia FAISD Handbook - Safety Directions", "Australia Exposure Standards", "FisherTransport Information","Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "OSPAR National List of Candidates for Substitution - Norway", "Australia Hazardous Waste Act - List A Wastes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail -Table A: Dangerous Goods List - RID 2013 (Dutch)", "OECD Existing Chemicals Database", "Sigma-AldrichTransport Information", "Australia High Volume Industrial Chemical List (HVICL)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)","Australia Dangerous Goods Code (ADG Code) -Dangerous Goods List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Appendix E (Part 2)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Hazardous Substances Information System - Consolidated Lists", "International Fragrance Association (IFRA) Survey: Transparency List"

hydrocarbon propellant(68476-85-7.) is found on the following regulatory lists

"International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code)","Australia - Victoria Occupational Health and Safety Regulations -Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 1","International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index","Australia Exposure Standards", "Australia -Tasmania - Work Health and Safety Regulations 2012 - Hazardous Chemicals at Major Hazard Facilities (and their Threshold Quantity) - Table 15.1","Australia - New South Wales - Work Health and Safety Regulation 2011 -Hazardous chemicals at major hazard facilities (and their threshold quantity) - Table 15.1", "Australia - South Australia - Work Health and Safety Regulations 2012 - Schedule 15—Hazardous chemicals at major hazard facilities (and their threshold quantity) Table 15.1","Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia - New South Wales - Work Health and Safety Regulation 2011 - Hazardous chemicals". "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)","OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)","Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Numbering System for Food Additives", "International Air Transport Association (IATA) Dangerous Goods Regulations -Prohibited List Passenger and Cargo Aircraft", "International Chemical Secretariat (ChemSec) SIN List (*Substitute It Now!)","International Society of Automotive Engineers (SAE) Declarable Substances Chemical List -ARP9536","Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved Gases","Australia High Volume Industrial Chemical List (HVICL)","United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)","Australia Dangerous Goods Code (ADG Code) -Dangerous Goods List", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals at major hazard facilities and their threshold quantity", "International Air Transport Association (IATA) Dangerous Goods

Chemwatch: 5147-39 Page 10 of 10 Issue Date: 24/07/2014 Version No: 2.1.1.1

DUBL-CHEK BO-1 Aerosol

Print Date: 31/07/2014

Regulations", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals at major hazard facilities (and their threshold quantity)"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.