



∑ 98 x 62mm View Size

Get clear visibility in every situation. The 98x62mm viewing area lets you see every weld with complete clarity.

Backup Battery

Dual CR2032 backup batteries improves the performance and reliability of the auto-darkening filter.

A 4 Point Harness

Get the perfect fit and stay comfortable for hours. Adjust all 4 points of contact to suit you, and have the weight spread more evenly, minimising neck strain.

● 1/1/1/1 Classification

Superior optical clarity with a 1/1/1/1 classification. Get an Auto-Darkening Filter (ADF) that's scored top marks across the board for a crystal-clear view of your weld at every angle.

External Grind Button

Seamlessly switch to grind mode with the click of a button. When the helmet is in grind mode a small LED will illuminate, so you don't need to take the helmet off to check.

☆4 Arc Sensors


Detect every arc instantly. The four optimally positioned arc sensors trigger the lens, darkening it and keeping your eyes shielded from the start, even when you're out of position.

ELITEVISION. Lens Technology

See your weld clearly in true colour. EliteVision technology allows more colours from the spectrum to pass through the view, giving you better optical clarity and reducing eye fatigue.

1:1 Scale

110mm x 90mm





Specifications

PARAMETER	VALUES	PARAMETER	VALUES	PARAMETER	VALUES
Filter Dimensions	110x90x9mm	UV/IR Protection	DIN15	Operating Temperature	-5°C to 65°C
View Size	98x62mm	Time from Light to Dark	0.08ms	Storage Temperature	-20°C to 65°C
Arc Sensors	4	Time from Dark to Light	0.2-1.1s	Shade Control	Yes (Internal)
Classification	1/1/1/1	Sensitivity Delay	Adjustable	Grind Mode	Yes (External)
Light State	3	Power Supply	Solar Cells & 2 x CR2032 Replaceable Batteries	Minimum TIG Amperage	5A
Dark State	5-13	Warranty	3 Years	Standards	AS/NZS 1337.1 B (High Impact) AS/NZS 1338.1 (Auto-Darkenin